

Alpha T30 Temperature USB PDF Data Logger



Auto PDF Report with Embedded Data

(1)

TEMPSEN

ALPHA

T30

www.tempsen.com

Automatically generating encrypted PDF format report, no software required to obtain data, embedded raw data allows analyzing report via TempCentre and Cold Chain Cloud.



Repeat start function enables quick start on site



Multiple Alarm Ranges

Up to 5 alarm ranges offer precise and intuitive statistics for each configured alarm range.



EN12830 Compliant

Complies to EN12830:1999 for transport, storage and distribution of chilled, frozen, deep frozen, guick-frozen food and others.



Extra Long Battery Life

101 101

Up to 900 days battery life offers long-term continuous recording possibilities.

monitoring for

Life Science



Online configuration without software

In support of online configuration without needing to download and install any specific software.



Mark Function

Click Mark button to write in time stamp for events requiring special attention during shipment, up to 9 marks available.



TempCentre 2.0 Support

Work with TempCentre 2.0 desktop software to easily and accurately view, analyze, archive and share data recorded from transport and storage, and achieve 21 CFR 11 compliance.







SPECIFICATIONS

Туре	Multi-use
Sensor	Internal NTC
Memory Capacity	28800 readings
Measurement Range	-30°C70°C (-22°F158°F)
Accuracy	±0.5°C/0.9°F
Resolution	0.1°C /°F
Start Mode	Manual/Auto/Temperature start
Logging Interval	1 minute2 hours
Logging Mode	Start&Stop/Loop
Alarm Range	High and low alarm/5 alarm ranges
Alarm Type	Single Event/Cumulative Alarm
Battery	3.6V lithium battery
Typical Run Time	900 days
Shelf Life	1 year
Display	Multi-function LCD •OK(√), Alarm(x), Running status •Temperature statistics (max, min, avg) •Limit violation event indication •Duration time of each alarm zone •Mark history
Button	Start/Stop/Mark/View
Connection	USB 2.0 Connector
Data Specification	•Temperature •Date/Time •Mark
Automatic Data File	Encrypted PDF report with embedded raw data
Software	TempCentre 2.0 (21 CFR 11 Compliance)
Compatible OS	WIN XP/7/8
Calibration	Factory NIST traceable 3-point calibration
Certifications	CE, EN12830, RTCA-DO160G (FAA Compliance)
Dimensions	107mm L x 48mm W x 12mm H
Weight	Approx. 65g
Packaging/Material	Case/Polycarbonate
Protection Class	IP54

50 ml

TempSen Electronics Company, a leading provider of data loggers & data acquisition systems headquartered in Shanghai, China, is committed to continuously offering a broad range of temperature monitoring devices and solutions for food and pharmaceutical industries, helping users employ stringent and effective monitoring measures for temperature sensitive goods in transit and storage. TempSen reserves the right to change any specifications and information about products without prior notice. TempSen, ITAG, Tempod are registered trademarks of TempSen Electronics Company. All other trademarks mentioned herein are property of their respective companies.

